PDU SM-1688

PDU SM-1688

The **PDU** (**P**ower **D**istribution **U**nit) **SM-1688** is a switchable power board for 19” server cabinet, which can be operated through web interface and SNMP.

So that all the 8 outputs can be switched on and off individually and the individual current consumption, the individual voltage, the individual power and total power factor can also be showed through web interface.

The 8 outputs can be directly selected on the display and switched on and off by pushing the button. The current of the selected output can also be showed.

Furthermore, the PDU **SM-1688** can be connected to an external sensor to monitor the temperature and the humidity through web interface.

Errors excepted. No warranty for the correctness of the information State: 18.06.2013

PDU SM-1688

Specification

Connector	Power In (C20): 1 Power Out (C13): 8 RJ11 (PDU Bus): 1
Controls	Automatic Cutout
LED / LED Display	Power Link Range
Materials	1.2mm Steel
Packing Unit	Shipping Unit: 1 piece
Guarantee and Warranty	24 Months Warranty
Article Number	88887071
EAN-Code	4260133125292
Scope of Delivery	Mounting Kit Connection Cable C20/C19 (2m) "PDU Utility", German and English User Manual on CD
Features	Measurement of Current, Voltage and Output Web Interface http, HTTPS, SNMP, DHCP, UDP, PFC, Adjustable Alarm Function Optional: Sensor to measure temperature and humidity (Article: 88887077)

Dimensions and Weight

	Article	Package
Height	45mm	88mm
Width	432mm	505mm
Depth	165mm	210mm

Weight (net): 2.875 kg
Weight (gross): 3.715 kg

Certification:

Errors excepted. No warranty for the correctness of the information State: 18.06.2013